

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : GREASE POWER
UFI : MW03-10SS-X00A-RUWD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent
Restrictive information: Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH
Rheinallee 96
55120 Mainz
Telephone : +49613196403
Telefax : +4961319642414
E-mail address : Produktsicherheit@werner-mertz.com
Responsible/issuing person :
Contact person : Product development / product safety

1.4 Emergency telephone number

+49(0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

Precautionary statements : P102 Keep out of reach of children.

Prevention:

P260 Do not breathe spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection.

Response:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Disposal:

P501

Dispose of container into the collection of recyclables only when it is completely empty.

Hazardous components which must be listed on the label:

sodium hydroxide

Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|--|--|--|--------------------------|
| Substances with a workplace exposure limit : | | | |
| (2-methoxymethylethoxy)propanol | 34590-94-8 252-104-2 01-2119450011-60 | | >= 2 - < 5 |
| 2,2'-methyliminodiethanol | 105-59-9 203-312-7 603-079-00-5 01-2119488970-24 | Eye Irrit. 2; H319 | >= 5 - < 10 |
| 1-butoxypropan-2-ol | 5131-66-8 225-878-4 603-052-00-8 01-2119475527-28 | Eye Irrit. 2; H319 Skin Irrit. 2; H315 specific concentration limit Eye Irrit. 2; H319 > 20 % Skin Irrit. 2; H315 > 20 % | >= 2 - < 5 |
| Decanol, ethoxylated | 26183-52-8 500-046-6 | Eye Irrit. 2; H319 Acute Tox. 4; H302 | >= 2 - < 5 |
| sodium octyl sulphate | 142-31-4 205-535-5 01-2119966154-35 | Skin Irrit. 2; H315 Eye Dam. 1; H318 specific concentration limit Eye Irrit. 2; H319 | >= 1 - < 2 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

| | | | |
|---------------------------|--|---|------------|
| | | 10 - < 20 % Eye Dam. 1; H318 >= 20,0 % | |
| sodium hydroxide | 1310-73-2 215-185-5 011-002-00-6 01-2119457892-27 | Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318 specific concentration limit Skin Corr. 1A; H314 >= 5 % Skin Corr. 1B; H314 2 - < 5 % Skin Irrit. 2; H315 0,5 - < 2 % Eye Irrit. 2; H319 0,5 - < 2 % | >= 1 - < 2 |
| Silicic acid, sodium salt | 1344-09-8 215-687-4 01-2119448725-31 | Eye Dam. 1; H318 Skin Irrit. 2; H315 | >= 1 - < 2 |
| Decan-1-ol.ethoxylated | 26183-52-8 500-046-6 | Eye Irrit. 2; H319 | >= 1 - < 2 |

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
Protect unharmed eye.
Continue rinsing eyes during transport to hospital.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : corrosive effects

Risks : No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons Information Service.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Neutralise with acid. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations", Refer to section 15 for specific national regulation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---------------------------------|--|-------------------------------|---------------------------------|------------|
| (2-methoxymethylethoxy)propanol | Not Assigned | TWA | 50 ppm 308 mg/m ³ | 2000/39/EC |
| | Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | |
| | | TWA | 50 ppm 308 mg/m ³ | |
| | Further information: Dermal absorption possible | | | |
| | | | 100 ppm | |
| | Further information: Dermal absorption possible | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

| | | | |
|--|---|----------------------------------|--|
| | STEL | 150 ppm | |
| | Further information: Dermal absorption possible | | |
| | | 100 ppm | |
| | Further information: Recommended exposure limit | | |
| | STEL | 150 ppm 900 mg/m ³ | |
| | STEL | 50 ppm 310 mg/m ³ | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|---------------------------------|-----------|-----------------|----------------------------|-----------------------|
| 2,2'-methyliminodiethanol | Workers | Inhalation | Long-term systemic effects | 7,9 mg/m ³ |
| | Workers | Dermal | Long-term systemic effects | 5,6 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 0,4 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 0,67 mg/kg |
| | Consumers | Oral | Long-term systemic effects | 0,13 mg/kg |
| 1-butoxypropan-2-ol | Workers | Inhalation | Long-term systemic effects | 147 mg/m ³ |
| | Workers | Skin contact | Long-term systemic effects | 52 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 43 mg/m ³ |
| | Consumers | Dermal | Long-term systemic effects | 22 mg/kg bw/day |
| | Consumers | Ingestion | Long-term systemic effects | 12,5 mg/kg bw/day |
| (2-methoxymethylethoxy)propanol | Workers | Skin contact | Long-term systemic effects | 65 mg/kg |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

| | | | | |
|-----------------------|-----------|--------------|--|------------|
| | Workers | Inhalation | Long-term systemic effects | 310 mg/m3 |
| | Consumers | Skin contact | Long-term systemic effects | 15 mg/kg |
| | Consumers | Ingestion | Long-term systemic effects | 1,67 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 37,2 mg/m3 |
| | Workers | Inhalation | Long-term systemic effects | 308 mg/m3 |
| | Workers | Skin contact | Long-term systemic effects | 283 mg/kg |
| | Consumers | Skin contact | Long-term systemic effects | 121 mg/kg |
| | Consumers | Ingestion | Long-term systemic effects | 36 mg/kg |
| sodium octyl sulphate | Workers | Skin contact | Long-term systemic effects | 4060 mg/kg |
| | Workers | Inhalation | Long-term systemic effects | 285 mg/m3 |
| | Consumers | Skin contact | Long-term systemic effects | 2440 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 85 mg/m3 |
| | Consumers | Ingestion | Long-term systemic effects | 24 mg/kg |
| sodium hydroxide | Workers | Inhalation | Long-term local effects | 1,0 mg/m3 |
| | Workers | Inhalation | Long-term systemic effects, Long-term local effects | 1,5 mg/m3 |
| | Workers | Inhalation | Short-term exposure, Local effects, Systemic effects | 3 mg/m3 |
| | Consumers | Inhalation | Long-term local effects, Long-term systemic effects | 0,6 mg/m3 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

| | | | | |
|---------------------------|-----------|--------------|--|-------------------|
| | Consumers | Inhalation | Short-term exposure, Local effects, Systemic effects | 1,2 mg/m3 |
| | Consumers | Ingestion | Long-term local effects, Long-term systemic effects | 25 mg/m3 |
| Silicic acid, sodium salt | Workers | Skin contact | Long-term systemic effects | 1,59 mg/kg bw/day |
| | Workers | Inhalation | Long-term systemic effects | 5,61 mg/m3 |
| | Consumers | Skin contact | Long-term systemic effects | 0,8 mg/kg bw/day |
| | Consumers | Inhalation | Long-term systemic effects | 1,38 mg/m3 |
| | Consumers | Ingestion | Long-term systemic effects | 0,8 mg/kg bw/day |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|---------------------------|---------------------------|-------------|
| 2,2'-methyliminodiethanol | Fresh water | 1 mg/l |
| | Marine water | 0,0045 mg/l |
| | Fresh water | 0,278 mg/l |
| | Marine water | 0,0278 mg/l |
| | Intermittent use/release | 1 mg/l |
| | Fresh water sediment | 2,17 mg/kg |
| | Marine sediment | 0,217 mg/kg |
| | Soil | 0,27 mg/kg |
| | STP | 10 mg/l |
| 1-butoxypropan-2-ol | Fresh water | 0,525 mg/l |
| | Marine water | 0,0525 mg/l |
| | Fresh water sediment | 2,36 mg/kg |
| | Marine sediment | 0,236 mg/kg |
| | Soil | 0,16 mg/kg |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

| | | |
|--|----------------------|--------------|
| | STP | 10 mg/l |
| | intermittent release | 5,25 mg/l |
| 1,2,3-Propanetricarboxylic acid, 2-hydroxy-, trisodium salt, dihydrate | Fresh water | 0,44 mg/l |
| | Marine water | 0,044 mg/l |
| | STP | 1000 mg/l |
| | Fresh water sediment | 34,6 mg/kg |
| | Marine sediment | 3,46 mg/kg |
| | Soil | 33,1 mg/kg |
| (2-methoxymethylethoxy)propanol | Fresh water | 19 mg/l |
| | Marine water | 1,9 mg/l |
| | Fresh water sediment | 70,2 mg/kg |
| | Marine sediment | 7,02 mg/kg |
| | Soil | 2,74 mg/kg |
| | Water | 190 mg/l |
| | STP | 4168 mg/l |
| sodium octyl sulphate | Fresh water | 0,1357 mg/l |
| | Marine water | 0,01357 mg/l |
| | STP | 1,35 mg/l |
| | Fresh water sediment | 1,5 mg/kg |
| | Marine sediment | 0,15 mg/kg |
| | Soil | 0,22 mg/kg |
| Silicic acid, sodium salt | Fresh water | 7,5 mg/l |
| | Marine water | 1 mg/l |
| | intermittent release | 7,5 mg/l |
| | STP | 348 mg/l |

8.2 Exposure controls

Personal protective equipment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

Eye/face protection : Tightly fitting safety goggles

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Remove and wash contaminated clothing before re-use.

Respiratory protection : Not required; except in case of aerosol formation.

Recommended Filter type:

ABEK-P3-filter

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|------------------------------|---------------------|
| Physical state | : liquid |
| Colour | : red, clear |
| Odour | : characteristic |
| Melting point/freezing point | : No data available |
| Boiling point/boiling range | : No data available |
| Flammability (solid, gas) | : No data available |
| Flammability (liquids) | : No data available |
| Lower explosion limit | : No data available |
| Upper explosion limit | : No data available |
| Flash point | : does not flash |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

| | |
|--|--|
| Ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| pH | : ca. 13,2, 100 % at 20 °C |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : No data available |
| Water solubility | : soluble |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Vapour pressure | : No data available |
| Density | : ca. 1,053 g/cm ³ at 20 °C |
| Relative density | : No data available |
| Relative vapour density | : No data available |
| Particle characteristics | : No data available |

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No decomposition if used as directed.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Our company is strongly against animal testing.

Our company does not place any orders for animal testing for the finished product or the ingredients.

However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Acute oral toxicity : LD50 (Dog): 7.500 mg/kg
LD50 (Rat): 5.130 mg/kg
LD50 (Rat): 5.135 mg/kg

Acute inhalation toxicity : LC50 (Rat): 55 - 60 mg/l
Exposure time: 4 h
LC50 (Rat): 3,35 mg/l
Exposure time: 7 h

Acute dermal toxicity : LD50 Dermal (Rabbit): 19.000 mg/kg
LD50 Dermal (Rat): 9.500 mg/kg
LD50 (Rabbit): 9.510 mg/kg
LD50 (Rabbit): 14.000 mg/kg

2,2'-methyliminodiethanol

105-59-9:

Acute oral toxicity : LD50 (Rat): 4.680 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
LD50 (Rabbit): 5.990 mg/kg

1-butoxypropan-2-ol

5131-66-8:

Acute oral toxicity : LD50 Oral (Rat, male and female): 3.300 mg/kg
Method: see user defined free text

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

LD50 (Rat): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 651 mg/l
Exposure time: 4 h

LC50 (Rat): 3,5 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402

Decanol, ethoxylated

26183-52-8:

Acute oral toxicity : LD50 Oral: > 2.000 mg/kg

sodium octyl sulphate

142-31-4:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402

sodium hydroxide

1310-73-2:

Acute oral toxicity : LD50 Oral (Rat): 2.000 mg/kg

Silicic acid, sodium salt

1344-09-8:

Acute oral toxicity : LD50 Oral (Rat): 3.400 mg/kg

Acute inhalation toxicity : LC50 (Rat): 2,06 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Remarks : No skin irritation

2,2'-methyliminodiethanol

105-59-9:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

Method : OECD Test Guideline 404
Result : No skin irritation

sodium octyl sulphate

142-31-4:

Result : Skin irritation

sodium hydroxide

1310-73-2:

Result : Corrosive

Silicic acid, sodium salt

1344-09-8:

Result : Skin irritation

Serious eye damage/eye irritation

Product:

Remarks : May cause irreversible eye damage.

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Result : No eye irritation

2,2'-methyliminodiethanol

105-59-9:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritating to eyes.

sodium octyl sulphate

142-31-4:

Result : Causes serious eye damage.

sodium hydroxide

1310-73-2:

Result : Corrosive

Silicic acid, sodium salt

1344-09-8:

Method : OECD Test Guideline 405
Result : Causes serious eye damage.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

Respiratory or skin sensitisation

Product:

Remarks : No data available

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Result : Does not cause skin sensitisation.

2,2'-methyliminodiethanol

105-59-9:

| | | |
|--------------------------|---|--|
| Species | : | Guinea pig |
| Method | : | OECD Test Guideline 406 |
| Result | : | Does not cause skin sensitisation. |
| Germ cell mutagenicity | : | Not Rated |
| Carcinogenicity | : | Not Rated |
| Reproductive toxicity | : | Not Rated |
| STOT - single exposure | : | The substance or mixture is not classified as specific target organ toxicant, single exposure. |
| STOT - repeated exposure | : | The substance or mixture is not classified as specific target organ toxicant, repeated exposure. |

Repeated dose toxicity

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

| | | |
|-------------------|---|-------------|
| Species | : | Rat |
| NOAEL | : | 1.000 mg/kg |
| Application Route | : | Oral |
| Exposure time | : | 28 d |

sodium octyl sulphate

142-31-4:

| | | |
|-------------------|---|-------------------------|
| Species | : | Rat |
| NOAEL | : | 488 mg/kg |
| Application Route | : | Oral |
| Method | : | OECD Test Guideline 408 |
| Species | : | Rat |
| LOAEL | : | 1016 mg/kg |
| Application Route | : | Oral |
| Method | : | OECD Test Guideline 408 |
| Species | : | Mouse |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

| | | |
|---------------------|---|-------------------------|
| NOAEL | : | 400 mg/kg |
| Application Route | : | Dermal |
| Method | : | OECD Test Guideline 411 |
| Aspiration toxicity | : | Not Rated |

11.2 Information on other hazards

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Toxicity to fish : (Pimephales promelas (fathead minnow)): > 10.000 mg/l
Exposure time: 96 h
Test Type: static test

(Poecilia reticulata (guppy)): > 1.000 mg/l
Exposure time: 96 h
Test Type: static test

(Fish): > 1.000 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.919 mg/l
Exposure time: 48 h
Test Type: static test

EC50 (Crangon crangon (shrimp)): > 1.000 mg/l
Exposure time: 96 h
Test Type: semi-static test

NOEC (Daphnia magna (Water flea)): > 0,5 mg/l
Exposure time: 22 d

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (microalgae)): > 969 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

(Selenastrum capricornutum): 1.000 mg/l
Exposure time: 72 h

EC50 (Skeletonema costatum (marine diatom)): 6.999 mg/l
Exposure time: 72 h

EC50 (Selenastrum capricornutum (green algae)): 969 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

NOEC (Pseudokirchneriella subcapitata (green algae)): 969 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): 4.168 mg/l
Exposure time: 18 h
Test Type: Growth inhibition

EC50 (No data available): > 100 mg/l

EC20 (activated sludge): > 1.000 mg/l
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 12 mg/l
Species: Daphnia magna (Water flea)

NOEC: > 0,5 mg/l
Exposure time: 22 d
Species: Daphnia magna (Water flea)

Lowest Observed Effect Concentration: > 0,5 mg/l
Exposure time: 22 d
Species: Daphnia magna (Water flea)

2,2'-methyliminodiethanol

105-59-9:

Toxicity to fish

: (Leuciscus idus (Golden orfe)): 1.466 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates

: (Daphnia magna (Water flea)): 233 mg/l
Exposure time: 48 h
Test Type: static test
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants

: NOEC (Desmodesmus subspicatus (green algae)): 6,25 mg/l
Exposure time: 72 h

EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to microorganisms

: EC20 (activated sludge): > 1.000 mg/l
Exposure time: 0,5 h
Method: OECD Test Guideline 209

1-butoxypropan-2-ol

5131-66-8:

Toxicity to fish

: LC50 (Poecilia reticulata (guppy)): 560 - 1.000 mg/l
Exposure time: 96 h

NOEC (Poecilia reticulata (guppy)): 180 mg/l
Exposure time: 96 h

LC50 (Fish): 1.000 mg/l
Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

EC50 (Fish): < 320 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 560 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (microalgae)): > 1.000 mg/l
Exposure time: 96 h
Test Type: Cell multiplication inhibition test

NOEC (Selenastrum capricornutum): 560 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Decanol, ethoxylated

26183-52-8:

Toxicity to fish

: LC50 : 1 - 10 mg/l
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates

: (Daphnia magna (Water flea)): 13,5 mg/l
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants

: (Desmodesmus subspicatus (green algae)): 12,0 mg/l
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to microorganisms

: EC0 (Bacteria): > 100 mg/l

sodium octyl sulphate

142-31-4:

Toxicity to fish

: LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants

: EC50 : > 100 mg/l
EC50 (Desmodesmus subspicatus (green algae)): > 511 mg/l
Exposure time: 72 h

Toxicity to microorganisms

: EC0 : > 100 mg/l

Toxicity to fish (Chronic toxicity)

: Lowest Observed Effect Concentration: > 1,357 mg/l
Exposure time: 42 d
Species: Pimephales promelas (fathead minnow)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity):
: NOEC: 1,4 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

sodium hydroxide

1310-73-2:

Toxicity to fish

: LC50 (Fish): 33 - 189 mg/l
Exposure time: 96 h

LC50 (Gambusia affinis (Mosquito fish)): 125 mg/l
Exposure time: 96 h

LC50 (Poecilia reticulata (guppy)): 76 mg/l
Exposure time: 24 h

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia (water flea)): 40,4 mg/l

EC50 (Daphnia magna (Water flea)): 76 mg/l
Exposure time: 24 h

EC50 (Ceriodaphnia (water flea)): 40,4 mg/l
Exposure time: 48 h
Test Type: Immobilization

Toxicity to microorganisms

: EC50 (Photobacterium phosphoreum): 22 mg/l
Exposure time: 15 min

Silicic acid, sodium salt

1344-09-8:

Toxicity to fish

: LC50 (Brachydanio rerio): 1.108 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 1.700 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to microorganisms

: EC0 (Pseudomonas putida): > 1.000 mg/l
Exposure time: 48 h

Decan-1-ol.ethoxylated

26183-52-8:

Toxicity to daphnia and other aquatic invertebrates

: EC50 (Daphnia (water flea)): 7,2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants

: EC50 (algae): 4,2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

12.2 Persistence and degradability

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Biodegradability

: Result: Readily biodegradable.

Biodegradation: > 70 %

Exposure time: 28 d

Method: OECD 301 E

Biodegradation: 75 %

Exposure time: 28 d

Method: OECD 301 F

Biodegradation: 93 %

Exposure time: 13 d

Method: OECD 302 B

Biodegradation: 91 %

Exposure time: 28 d

Method: EN ISO 14593: CO2-Headspace-Test

Biodegradation: 75 %

Exposure time: 10 d

Method: OECD 301 F

2,2'-methyliminodiethanol

105-59-9:

Biodegradability

: Result: rapidly biodegradable

Biodegradation: 96 %

Exposure time: 18 d

Method: OECD 301 A

1-butoxypropan-2-ol

5131-66-8:

Biodegradability

: Biodegradation: 90 %

Exposure time: 28 d

Method: OECD 301 E

Remarks: Readily biodegradable, according to appropriate OECD test.

Decanol, ethoxylated

26183-52-8:

Biodegradability

: Biodegradation: 89 %

Exposure time: 28 d

Method: OECD 301 F

sodium octyl sulphate

142-31-4:

Biodegradability

: Biodegradation: 98,2 %

Remarks: Expected to be biodegradable

sodium hydroxide

1310-73-2:

Biodegradability

: Result: Biodegradable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

Remarks: The methods for determining the biological degradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).
Partition coefficient: n-octanol/water : log Pow: 1,01

1-butoxypropan-2-ol

5131-66-8:

Bioaccumulation : Bioconcentration factor (BCF): < 100
Remarks: Does not bioaccumulate.
Partition coefficient: n-octanol/water : log Pow: 3,2
log Pow: 1,2 (20 °C)
pH: 7

sodium hydroxide

1310-73-2:

Bioaccumulation : Species: Fish
Remarks: No bioaccumulation is to be expected (log Pow <= 4).

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

(2-methoxymethylethoxy)propanol

34590-94-8:

Assessment : This substance is not considered to be very persistent and very bioaccumulating (vPvB).. This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

SECTION 13: Disposal considerations

13.1 Waste treatment methods

| | |
|------------------------|---|
| Product | : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. In accordance with local and national regulations. |
| Contaminated packaging | : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. |
| Waste Code | European Waste Catalogue 20 01 29* According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. |

SECTION 14: Transport information

14.1 UN number or ID number

| | | |
|------|---|------|
| ADR | : | 3267 |
| IMDG | : | 3267 |
| IATA | : | 3267 |

14.2 UN proper shipping name

| | | |
|------|---|--|
| ADR | : | CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (sodium hydroxide) |
| IMDG | : | CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (sodium hydroxide) |
| IATA | : | Corrosive liquid, basic, organic, n.o.s. |

14.3 Transport hazard class(es)

| | | |
|------|---|---|
| ADR | : | 8 |
| IMDG | : | 8 |
| IATA | : | 8 |

14.4 Packing group

| | | |
|------------------------------|---|--|
| ADR | | |
| Classification Code | : | C7 |
| Packaging group | : | III |
| Hazard Identification Number | : | 80 |
| Labels | : | 8 |
| Tunnel restriction code | : | (E) |
| IMDG | | |
| Packaging group | : | III |
| Labels | : | 8 |
| EmS Number | : | F-A, S-B |
| IATA | | |
| (Cargo) | : | Corrosive liquid, basic, organic, n.o.s. |
| (Passenger) | : | Corrosive liquid, basic, organic, n.o.s. |
| Packaging group | : | III |
| Labels | : | 8 |

14.5 Environmental hazards

ADR

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

For personal protection see section 8.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

TA Luft List (Germany) : Total dust: Not applicable
: Inorganic substances in powdered form: Not applicable
: Inorganic substances in vapour or gaseous form: portionClass 3: 0,02 %
: Organic Substances: Not applicable
: Carcinogenic substances: Not applicable
: Mutagenic: Not applicable
: Toxic to reproduction: Not applicable

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Update: Percent volatile: 5 %
296,16 g/l
VOC content excluding water

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Update: Percent volatile: 5 %
52,7 g/l
VOC content valid only for coating materials used on wood surfaces

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

according to Detergents
Regulation EC 648/2004 : <5% anionic surfactants, non-ionic surfactants

GISBAU (D) : GG 80

15.2 Chemical safety assessment

SECTION 16: Other information

Full text of H-Statements

H290 : May be corrosive to metals.
H302 : Harmful if swallowed.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Met. Corr. : Corrosive to metals
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2000/39/EC / TWA : Limit Value - eight hours

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways;
ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended



Tana-Chemie GmbH
Werner & Mertz Group

GREASE POWER

WM 0713654

Order number: 0713654

Version 9.13

Revision Date 13.03.2025

Print Date 06.08.2025

TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|---------------|------|
| Skin Corr. 1A | H314 |
| Eye Dam. 1 | H318 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Based on product data or assessment |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REG_EU / EN

500000004242