



FIT





COLD



GRIP

X-GRIP THERMO

51-850



CHARACTERISTICS

- Latex foam coating on the palm and fingers
- Acrylic terry liner (10 gauge)
- Seamless glove
- Elastic knitted wrist cuff
- Fully coated thumb for extra safety
- The brushed inner lining is soft and comfortable and keeps your hands warm in extremely low temperatures
- Optimum comfort during prolonged use
- Excellent grip, even when working in wet, oily and greasy conditions
- Excellent ventilation on the back of the hand, ensuring a good absorption of perspiration
- The orange fluorescent colour of the liner provides excellent visibility

Article number: 1.51.850.00

SUITABLE FOR ACTIVITIES IN E.G.

- Construction
- Scaffolding
- Government services
- Transport & logistics
- Recycling
- Civil and hydraulic engineering
- Agriculture
- Shipping

COLOUR

Grey/fluorescent orange

SIZES

8/M to 11/XXL incl.

PACKAGING

- 1 pair per polybag
- 12 pairs per bundle
- 72 pairs per outer box

EN388:2016+A1:2018



2242X

EN511:2006



X2X



EN ISO 21420:2020

PRODUCT INFORMATION

SIZE	ARTICLE NO.	EAN CODE 1 PAIR (POLYBAG)	EAN CODE 12 PAIRS (BUNDLE)	EAN CODE 72 PAIRS (OUTER BOX)
8/M	1.51.850.08	8718249037825	8718249037832	8718249037849
9/L	1.51.850.09	8718249027468	8718249027475	8718249027482
10/XL	1.51.850.10	8718249027499	8718249027505	8718249027512
11/XXL	1.51.850.11	8718249027529	8718249027536	8718249027543

COLOUR BINDING/OVERLOCKING

Sizes	8/M	9/L	10/XL	11/XXL
Colour binding/overlocking	green	blue	grey	black

CLARIFICATION OF PICTOGRAMS

EN388: 2016+A1:2018



2242X

EN388:2016+A1:2018



abcdef

Protection against mechanical hazards

A = Scuff resistance (0-4)
B = Cut resistance (0-5)
C = Tear resistance (0-4)
D = Puncture resistance (0-4)
E = Cut resistance (in accordance with EN ISO 13977 (A to F))
F = Impact resistance (optional) (P = Passed)

EN511:2006



X2X

EN511:2006



abcdef

Protection against cold

A = Radiative cooling (0-4)
B = Contact cold (0-4)
C = Watertightness (0-1)

Note: X = untested or not applicable

STORAGE CONDITIONS

The gloves should be kept in a clean, cool and dry place and not kept compressed in their original packaging. Do not expose the gloves to direct sunlight. Make sure that the packaging and the gloves are not damaged during shipping.

TESTING INSTITUTE

These gloves are certified by: CTC (Notified Body no. 0075), 4 Rue Hermann Frenkel 69367 Lyon, Cedex 07, France

DECLARATION OF CONFORMITY

For a copy of the declaration of conformity, we refer you to the following link: www.oxxa-safety.com/doc

YOUR SUPPLIER:

RELATED PRODUCTS



OXXA X-FROST 51-860

Art. no. 1.51.860.00



OXXA X-GRIP 51-000

Art. no. 1.51.000.00