




New Design – Water & Oil repellent, cut protection level E, soft and comfortable, nitrile.

KEY FEATURES

- New Design – high quality level E cut protection glove with great abrasion resistance.
- Water and oil repellent palm, makes it ideal for both dry and wet working conditions.
- Soft and comfortable. Great dexterity, flexibility and good fitting.
- ANSI Cut level A5.
- 10-finger touch screen functionality enables you to use all touch screen device without taking off the glove on the jobs, more safe and easier.
- Contact heat protection up to 250 °C according to EN407.
- Brand promotion price.



PRODUCT DETAILS

Liner	Cut resistant yarn
Gauge	13
Coating	Nitrile
Finishing	Foam
Colour	Green / Black
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose or works with high cut hazard or contact heat hazard in dry, wet and oil conditions.

Such as handling parts with sharp or rough edges, assembly, inspection, packaging, metal sheet works, construction, general handling...



CERTIFICATION

CE EN ISO 21420:2020+A1:2018

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to max. 5): **X**
Tear (min.0 to max. 4): **3**
Puncture (min.0 to max. 4): **2**
Cut resistance from sharp objects EN ISO
13997:1999 (min. A to max. F, X - not tested): **E**
Impact protection (P if pass, F if failed): **-**

EN388:2016



EN ISO 21420:2020+A1:2018 Dexterity (min.0 to max.5):
level 5.

**EN407:2020 Heat protection:
levels obtained in laboratory tests**

A - Limited flame spread X of 4
B - Contact heat: 2 of 4
C - Convective heat: X of 4
D - Radiant heat: X of 4
E - Small splashes of molten metal: X of 4
F - Large quantities of molten metal: X of 4

EN407:2020



X = not tested or testing method is unsuitable for the design
of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-361 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

