



Water and oil repellent, flexible and comfortable. 13 gauge, cut protection level D, sandy nitrile.

KEY FEATURES

- Water and oil repellent, cut protection level D.
- Sandy finish provides super grip in oily and dry working condition.
- Great flexibility, comfort and good fit.
- Contact heat protection up to 100 °C according to EN407.



PRODUCT DETAILS

Liner	UHMWPE mixed with other yarns
Gauge	13
Coating	Nitrile
Finishing	Flat & Sandy
Colour	Red / Purple & Black
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020


RECOMMENDED APPLICATIONS

General purpose or works with high cut hazard or contact heat hazard in oily or wet conditions.

Such as oil or fluids or other liquid (not chemicals) change, equipment maintenance, recycling, press shop works, inspection, assembly, sheet metal work, work with sharp or rough edge parts...



CERTIFICATION



Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to max. 5):	X
Tear (min.0 to max. 4):	4
Puncture (min.0 to max. 4):	4
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	D
Impact protection (P if pass, F if failed):	-

EN388:2016



4X44D

EN407:2020 Heat protection: levels obtained in laboratory tests

A - Limited flame spread:	X of 4
B - Contact heat:	1 of 4
C - Convective heat:	X of 4
D - Radiant heat:	X of 4
E - Small drops of molten metal:	X of 4
F - Large quantity of molten metal:	X of 4

EN407:2020



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-369 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals or electrical risk.
Please ensure the products are strictly used within their protection levels.

