



13 gauge cut level D glove with sandy nitrile coating, premium quality leather in the palm. Extra softness. Heat & oil resistance.

KEY FEATURES

- High quality cut protection level D glove with great flexibility and comfort.
- Premium soft and comfortable leather in the palm offers great puncture protection, more durable and a higher contact heat protection.
- The nitrile coating contributes to great oil resistance and extra heat protection.
- Good fitting.



PRODUCT DETAILS

| | |
|---------------|--------------------------------|
| Liner | UHMWPE, glass fiber, polyamide |
| Gauge | 13 |
| Coating | Nitrile |
| Finishing | Sandy |
| Colour | Grey / Black |
| Size | 7,8,9,10,11 |
| Packing | 6 pairs/pack, 72 pairs/carton |
| Tariff number | 61161020 |

RECOMMENDED APPLICATIONS

General purpose or works with high cut hazard or puncture hazard or contact heat hazard in dry or light wet/oily conditions.

Such as handling sharp or rough parts, metal & sheet metal works, stamping press works and etc.



CERTIFICATION


CE EN21420:2020

Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to max. 5): **X**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **4**
Cut resistance from sharp objects EN ISO
13997:1999 (min. A to max. F, X - not tested): **D**
Impact protection (P if pass, F if failed): **-**

EN388:2016



4X44D

EN407:2020 Heat protection: levels obtained in laboratory tests

A - Limited flame spread: X of 4
B - Contact heat: 2 of 4
C - Convective heat: X of 4
D - Radiant heat: X of 4
E - Small splashes of molten metal: X of 4
F - Large quantities of molten metal: X of 4

EN407:2020



X2XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-372 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.
Never wear gloves when operating machinery with accessible rotating or other moving parts.

