



Premium quality 13 gauge cut level F glove. High visibility, soft, flexible and comfortable, sandy nitrile. Reinforced in the crotch.

## KEY FEATURES

- Premium quality cut protection level F / A6 glove with great abrasion resistance.
- High visibility yellow provides extra safety in challenging light conditions and easy to recognise.
- Reinforcement greatly extends glove life to save your cost and provides extra protection in the weakest area.
- Sandy finish provides super grip in oily and dry working condition.
- Soft, flexible and comfortable. Good fitting.
- 10-finger touch screen function enables you to use any touch screen devices during work.
- 360° breathability.
- Contact heat protection up to 100 °C according to EN407.



## PRODUCT DETAILS

Liner	UHMWPE, steel fiber and others
Gauge	13
Coating	Nitrile
Finishing	Sandy
Colour	Hi-vis Yellow / Black / Red
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

## RECOMMENDED APPLICATIONS

**General purpose or works with high cut hazard or contact heat hazard in dry or light oily conditions or challenging light conditions.**

Such as handling sharp or rough parts, outdoor works, automotive industry, mining, construction, metal sheet works, maintenance, assembly, inspection...



## CERTIFICATION

**CE** EN ISO 21420:2020

Category II

**EN388:2016 Mechanical protection:  
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	<b>4</b>
Blade cut - coupe test (Index) (min.0 to max. 5):	<b>X</b>
Tear (min.0 to max. 4):	<b>4</b>
Puncture (min.0 to max. 4):	<b>4</b>
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	<b>F</b>
Impact protection (P if pass, F if failed):	-

EN388:2016



4X44F

**EN407:2020 Heat protection:  
levels obtained in laboratory tests**

A - Limited flame spread:	X of 4
B - Contact heat:	1 of 4
C - Convective heat:	X of 4
D - Radiant heat:	X of 4
E - Small drops of molten metal:	X of 4
F - Large quantity of molten metal:	X of 4

EN407:2020



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

## STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-387 can normally be 5 years.

## CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

## WARNING

Don't use in case of chemicals or electrical risk.  
Please ensure the products are strictly used within their protection levels.  
Never wear gloves when operating machinery with accessible rotating or other moving parts.

