



Premium quality cut protection level D glove with extra leather palm, 15 gauge, nitrile.

KEY FEATURES

- Premium cut protection level D glove with great flexibility and comfort.
- Extra leather in the palm offers a much better puncture protection, more durable and a higher contact heat protection.
- Reinforcement in the crotch offers extra durability and more protection while working.
- Very flexible and a lighter weight of the glove liner contributes to more comfort and much less hand fatigue.
- Good fitting.



PRODUCT DETAILS

Liner	UHMWPE, recycled polyester
Gauge	15
Coating	Nitrile
Finishing	Foam
Colour	Dark Blue / Grey
Size	8,9,10,11
Packing	6 pairs/pack, 72 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose or works with high cut hazard or puncture hazard or contact heat hazard in dry or light wet/oily conditions.

Such as handling sharp or rough parts, metal & sheet metal works, stamping press works and etc.



CERTIFICATION

CE EN21420:2020+A1:2018

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to max. 5): **X**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **4**
Cut resistance from sharp objects EN ISO
13997:1999 (min. A to max. F, X - not tested): **D**
Impact protection (P if pass, F if failed): **-**

EN388:2016



4X44D

**EN407:2020 Heat protection:
levels obtained in laboratory tests**

A - Limited flame spread: X of 4
B - Contact heat: 2 of 4
C - Convective heat: X of 4
D - Radiant heat: X of 4
E - Small splashes of molten metal: X of 4
F - Large quantities of molten metal: X of 4

EN407:2020



X2XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-900LP can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.

