



18 gauge cut level B, XTech PU, second skin feeling, super flexible and dexterity, comfort and sensitivity.

KEY FEATURES

- One of the thinnest and finest cut level B glove with PU coating
- Perfect dexterity, fitting and flexibility makes it ideal for general cut protection works and also precision works.
- Much less hand fatigue and more productivity
- Special XTech PU offers a better grip performance and extra softness
- Very soft and comfortable



PRODUCT DETAILS

Liner	UHMWPE mixed with other yarns
Gauge	18
Coating	Special XTech PU
Finishing	XTech
Colour	Blue / Black
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161080


RECOMMENDED APPLICATIONS

General purpose or precision works with high cut hazard in dry or light oily conditions.

Such as precision works, assembly, handling parts with sharp or rough edges, maintenance, general handling, inspection, packaging, sorting...



CERTIFICATION

 EN21420:2020+A1:2018

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	3
Blade cut - coupe test (Index) (min.0 to max. 5):	X
Tear (min.0 to max. 4):	4
Puncture (min.0 to max. 4):	2
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	B
Impact protection (P if pass, F if failed):	-

EN388:2016



3X42B

EN21420:2020+A1:2018 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.
The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-930 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

