



## PRODUCT DETAILS

Liner	Nylon
Gauge	18
Coating	Nitrile
Finishing	Flat & Sandy
Colour	Grey / Purple & Black
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 120 pairs/carton
Tariff number	61161020

Water and oil repellent palm. Super flexible, dexterity and minimum hand fatigue. 18 gauge, double nitrile.

## KEY FEATURES

- Water and oil repellent palm, double nitrile coating makes it more durable and great abrasion resistance.
- The 18 gauge knitting liner, which is much thinner, more flexible and great dexter than popular 15 gauge grey nylon nitrile glove. The liner feels like a second skin.
- Minimum hand fatigue caused by glove.
- Sandy finish provides super grip in wet and dry working condition.
- Soft, comfortable and good fitting.
- Contact heat protection up to 100 °C according to EN407.

## RECOMMENDED APPLICATIONS

General purpose or precision works with/without contact heat hazard in wet or oily conditions.

Such as fine assembly and disassembly, equipment maintenance, cleaning, sorting, handling small parts, general works with water or oil, general handling, adjusting systems...



## CERTIFICATION

 EN21420:2020

Category II

**EN388:2016 Mechanical protection:  
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):

EN388:2016



4

1

2

1

X

-

Blade cut - coupe test (Index) (min.0 to max. 5):

Tear (min.0 to max. 4):

Puncture (min.0 to max. 4):

Cut resistance from sharp objects EN ISO

13997:1999 (min. A to max. F, X - not tested):

Impact protection (P if pass, F if failed):

EN21420:2020 Dexterity (min.0 to max.5):

**level 5.**

**EN407:2020 Heat protection:**

**levels obtained in laboratory tests**

A - Burning behaviour: X of 4

B - Contact heat: 1 of 4

C - Convective heat: X of 4

D - Radiant heat: X of 4

E - Small drops of molten metal: X of 4

F - Large quantity of molten metal: X of 4

EN407:2020



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

## STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-009P can normally be 5 years.

## CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

## WARNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.

